

1	2	3	4	5	6	7	8	9	10	11	12	13	14	
A	Steckerbelegung / PIN Assignment													A
B	P1 1 ----- 2 2 ----- 3 3 ----- 1 4 ----- 10 5 ----- 11 6 ----- 9 7 ----- 18 8 ----- 19 9 ----- 17 10 ----- 23 11 ----- 22 12 ----- 24 15 ----- 6 16 ----- 7 17 ----- 15 18 ----- 14 19 ----- 16 SHELL ----- SHELL													B
C														C
D														D
E														E
F														F
G				HDMI™/DVI-D Adapter - gegossenen Anschlüsse: max. Auflösung: Material: Kontakte: DVI-D-Stecker Dual-Link (24+1 pin), HDMI™-Buchse (Typ A) WQXGA (2560 x 1600) 60 Hz PVC vernickelt HDMI™/DVI-D adapter - moulded Connectors: max. Resolution: Material: Contacts: DVI-D plug Dual-Link (24+1 pin), HDMI™ jack (type A) WQXGA (2560 x 1600) 60 Hz PVC nickel plated										G
H														H
I	Änderungen			Datum		Name		Bezeichnung				Blatt		I
J	Datum		Name	gez.:	05.07.2021	rs	Adapter HDMI F/DVI-D (24+1pin) M 				1/1		J	
				gepr.:	05.07.2021	aw	Zeichnungs-Nr.:				von			
				Norm:			68482							
				Änderungen vorbehalten / Subject to change										
1	2	3	4	5	6	7	8	9	10	11	12	13	14	