



Datasheet

UACC-Adapter-PoE-USBC+UACC-G4-INS-Cable-USB-4.5M

G4 Instant PoE Adapter (4.5 m)



UACC-Adapter-PoE-USBC

Mechanical

Dimensions	Without cable: Ø30.4 x 95 mm (Ø1.2 x 3.7")
Weight	85 g (3 oz)
Enclosure material	Polycarbonate

Hardware

Ports	(1) Input: RJ45 (1) Output: USB Type-C
Power method	PoE
Input rating	48VDC, 0.25A
Output rating	5VDC, 2A
ESD/EMP protection	Contact: ±4kV Air: ±8kV
Compatible devices	Camera G4 Instant (UVC-G4-INS) G4 DoorBell Pro (UVC-G4-Doorbell-Pro)
Operating temperature	-10 to 40° C (14 to 104° F)
Operating humidity	5 to 90% noncondensing
Certifications	CE, FCC, IC

UACC-G4-INS-Cable-USB-4.5M

Specifications

Weight	117 g (4.1 oz)
Cable length	4.5 m (14.76 ft)
Cable color	White
Shielding type	Shielded twisted pair (STP)
Conductor wire gauge	(2) 24 AWG + (3) 30 AWG
Conductor type	Stranded copper
Jacket material	Thermoplastic elastomer (TPE)
Jacket diameter	3.5 mm (0.14 in)
Bend radius	Min. 14 mm (0.55 in)
Anti-crosstalk divider	No
Flam rating	VW-1 (UL1581)
Storage temperature	-40 to 85° C (-40 to 185° F)
Operating temperature	-20 to 60° C (-4 to 140° F)

