



APC Smart-UPS, Line Interactive, 2200VA, Rackmount 2U, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD



Brand : APC

Product code: SMT2200RMI2UNC

Product name : Smart-UPS, Line Interactive, 2200VA, Rackmount 2U, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD

Smart-UPS, Line Interactive, 2200VA, Rackmount 2U, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD

APC Smart-UPS, Line Interactive, 2200VA, Rackmount 2U, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD. UPS topology: Line-Interactive, Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: C13 coupler, C19 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 509 Ah, Battery recharge time: 5 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE

Features		Design	
UPS topology *	Line-Interactive	Product colour *	Black
Output power capacity *	2.2 kVA	Display type	LCD
Output power *	1980 W	LED indicators	✓
Waveform *	Sine	Operational conditions	
Input operation voltage (min) *	151 V	Operating temperature (T-T)	0 - 40 °C
Input operation voltage (max) *	302 V	Storage temperature (T-T)	-15 - 45 °C
Input frequency *	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (min)	220 V	Storage relative humidity (H-H)	0 - 95%
Output operation voltage (max)	240 V	Operating altitude	0 - 3000 m
Output frequency	50/60 Hz	Non-operating altitude	0 - 15000 m
Surge energy rating	375 J	Certificates	
Response time	4 ms	Compliance certificates	RoHS
Emergency Power Off (EPO)	0	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Noise level	55 dB	Packaging content	
Surge protection	✓	Rack mount kit	✓
Audible alarm(s)	✓	Cables included	Input power cable, USB cable
Web-based management	✓	Management card included	✓
Audible alarm modes	Battery replacement	Quick installation guide	✓
Auto-restart	✓	Sustainability	
Ports & interfaces		Sustainability certificates	Green Premium
AC outlet types	C13 coupler, C19 coupler	Weight & dimensions	
AC outlets quantity	9 AC outlet(s)	Width	480 mm
Number of output IEC jumpers	3	Depth	683 mm
USB 2.0 ports quantity	1	Height	86 mm
Ethernet LAN (RJ-45) ports	1	Weight	42.2 kg
SmartSlot	✓	Packaging data	
SmartConnect port	✗	Resource CD	✓
Battery		Package width	600 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	980 mm
Battery capacity	509 Ah	Package height	254 mm
Battery recharge time	5 h	Package weight	49.6 kg
Hot-swap battery	✓	Logistics data	
Automatic battery test	✓	Products per pallet	8 pc(s)
Cold start	✓	Harmonized System (HS) code	85078000
Design			
Form factor *	Rackmount		
Rack capacity	2U		

Logistics data

Total carbon footprint (kg of CO2e) 3327.3

Other features

Output voltage 230 V



0731304327691



731304327691

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.