

KYOCERA PA6000x 1200 x 1200 DPI A4

Brand : KYOCERA

Product code: 110COT3NL0

Product name : PA6000x

KYOCERA PA6000x. Print technology: Laser. Number of print cartridges: 1, Maximum duty cycle: 300000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 60 ppm, Duplex printing. Display: LCD. Network ready. Product colour: White



Printing		Network	
Duplex printing mode	Auto	Ethernet LAN data rates	10,100,1000 Mbit/s
Print resolution black	1200 x 1200 DPI	Near Field Communication (NFC)	✗
Colour *	✗	Bluetooth	✗
Print technology *	Laser	Security algorithms	HTTPS, IPPS, IPsec, SNMPv3
Duplex printing *	✓	Mobile printing technologies	Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service
Maximum resolution *	1200 x 1200 DPI	Performance	
Print speed (black, normal quality, A4/US Letter) *	60 ppm	Internal memory *	512 MB
Duplex print speed (black, normal quality, A4/US Letter)	43 ppm	Maximum internal memory	2500 MB
Warm-up time	25 s	Compatible memory cards	SD, SDHC
Time to first page (black, normal)	4.55 s	Built-in processor	✓
Features		Processor family	ARM Cortex
Maximum duty cycle *	300000 pages per month	Processor model	Cortex-A53
Recommended duty cycle	15000 - 30000 pages per month	Processor frequency	1400 MHz
Printing colours *	Black	Processor cores	2
Number of print cartridges *	1	Sound pressure level (printing)	57 dB
Page description languages *	Epson LQ, IBM ProPrinter, JPEG, OpenXPS, PCL 5e, PCL 6, PCL XL, PCLm, PDF, PWG, PostScript 3, TIFF, URF, XPS	Sound power level (standby)	33 dB
		Design	
Printer fonts	Barcode, Bitmap, PCL	Market positioning *	Business
Number of printer fonts	93	Product colour *	White
Replacement cartridges	TK-3440	Built-in display *	✓
Input & output capacity		Display	LCD
Total number of input trays *	1	Colour display	✗
Total input capacity *	500 sheets	Touchscreen	✗
Total output capacity *	500 sheets	Display number of lines	5 lines
Paper tray 1 input capacity	500 sheets	Control type	Buttons
Paper input type	Cassette, Paper tray	Certification	GS, TÜV, CE
Multi-Purpose tray	✓	Power	
Multi-Purpose tray input capacity	100 sheets	Power consumption (printing) *	710.2 W
Maximum number of input trays	5	Power consumption (standby)	9 W
Maximum input capacity	2600 sheets	Power consumption (PowerSave)	0.5 W
Maximum output capacity	500 sheets	AC input voltage	220 - 240 V
		AC input frequency	50 - 60 Hz
Paper handling		System requirements	
Maximum ISO A-series paper size *	A4	Windows operating systems supported	✓
Maximum print size	216 x 356 mm		
Paper tray media types *	Plain paper		
Multi-purpose tray media types	Legal, Letter		
ISO A-series sizes (A0...A9) *	A4, A5		
ISO B-series sizes (B0...B9)	B5		

Paper handling		System requirements	
Non-ISO print media sizes	Legal, Letter	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Custom media width	140 - 216 mm		
Custom media length	210 - 356 mm		
Paper tray media weight	60 - 120 g/m ²		
Multi-Purpose Tray media weight	60 - 220 g/m ²		
Duplex media weight	60 - 120 g/m ²		
Ports & interfaces		Linux operating systems supported	✓
Standard interfaces	RJ-45, USB 2.0	Other operating systems supported	ChromeOS
Direct printing *	✓	Sustainability	
USB port *	✓	Sustainability certificates	Blue Angel, ENERGY STAR, EPEAT Silver
USB 2.0 ports quantity	2	Weight & dimensions	
USB connector	USB Type-A / USB Type-B	Width	410 mm
Optional connectivity	Ethernet, Parallel, Wireless LAN	Depth	416 mm
Network		Height	363 mm
Network ready	✓	Weight	16.2 kg
Wi-Fi *	✗	Packaging data	
Ethernet LAN *	✓	Package width	549 mm
Cabling technology	10/100/1000Base-T(X)	Package depth	517 mm
		Package height	455 mm
		Package weight	20 kg
		Packaging content	
		Cartridge(s) included	✓
		Included cartridge capacity (black)	11000 pages
		Cables included	AC
		Technical details	
		Compliance certificates	CE, REACH, RoHS



0632983079904



632983079904

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.