

Fujitsu PRIMERGY TX1330 M5 server Tower Intel Xeon E E-2388G 3.2 GHz 32 GB DDR4-SDRAM 500 W



Brand : Fujitsu

Product family: PRIMERGY

Product code:
LKN:R1335S0006IN

Product name : TX1330 M5

Intel Xeon E-2388G, 32 GB, EP680i, Intel C256, 4 x USB 2.0, 1 x USB 3.2 Gen 1 (3.1 Gen 1) Type-A, 2 x USB 3.2 Gen 2 (3.1 Gen 2) Type-A, 1 x USB 3.2 Gen 2 (3.1 Gen 2) Type-C, 500W, 26.4 kg
Fujitsu PRIMERGY TX1330 M5. Processor family: Intel Xeon E, Processor frequency: 3.2 GHz, Processor model: E-2388G. Internal memory: 32 GB, Internal memory type: DDR4-SDRAM, Memory layout (slots x size): 1 x 32 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 500 W, Redundant power supply (RPS) support. Chassis type: Tower

Processor		Expansion slots	
Processor manufacturer *	Intel	PCI Express x4 (Gen 3.x) slots	2
Processor family *	Intel Xeon E	PCI Express x8 (Gen 4.x) slots	2
Processor model *	E-2388G	PCI slots	1
Processor frequency *	3.2 GHz	Design	
Processor boost frequency	4.6 GHz	Chassis type *	Tower
Processor cores	8	Product colour	Black
Processor cache	16 MB	Rack mounting	✓
Motherboard chipset	Intel C256	Redundant fans support	✓
Number of processors installed	1	Performance	
Maximum number of SMP processors	1	Noise level	22 dB
Memory		Trusted Platform Module (TPM)	✓
Internal memory *	32 GB	Trusted Platform Module (TPM) version	2.0
Internal memory type *	DDR4-SDRAM	Software	
Memory slots	4x DIMM	Operating system installed *	✗
ECC	✓	Compatible operating systems * Windows Server 2022 Datacenter, Windows Server 2022 Standard, Windows Server 2022 Essentials, Windows Server 2019 Datacenter, Windows Server 2019 Standard, Windows Server 2019 Essentials, VMware vSphere 7.0, Red Hat Enterprise Linux 8, Univention Corporate Server 4	
Memory clock speed	3200 MHz		
Memory layout (slots x size)	1 x 32 GB		
Maximum internal memory *	128 GB		
Storage		Power	
Supported HDD sizes	2.5"	Redundant power supply (RPS) support *	✓
RAID support *	✓	Power supply *	500 W
Hot-Plug support	✓	Power supply input voltage	100 - 240 V
Optical drive type *	✗	Power supply input frequency	50 / 60 Hz
Network		Operational conditions	
LAN controller	Intel I210	Operating temperature (T-T)	5 - 45 °C
Ethernet LAN	✓	Operating relative humidity (H-H)	10 - 85%
Cabling technology	10/100/1000Base-T(X)		
Ethernet interface type	Gigabit Ethernet		
Ports & interfaces			
Ethernet LAN (RJ-45) ports *	3		
USB 2.0 ports quantity	4		
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2		

Ports & interfaces		Certificates	
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2	Certification	CB, GS, CE, NRTLc/us, FCC, ICES-003, NMB-003, VCCI, JIS 61000-3-2, EAC, KC, CCC, RCM, BSMI
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1		
VGA (D-Sub) ports quantity	1		
DisplayPorts quantity	1	Sustainability	
Total number of SATA connectors	7	Sustainability compliance	✓
Weight & dimensions			
		Width	177.2 mm
		Depth	521.7 mm
		Height	456.2 mm
		Weight	26.4 kg
Technical details			
		Compliance certificates	RoHS, WEEE



4065221895817

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.