



Zebra ZE500 label printer 300 x 300 DPI 305 mm/sec Wired Ethernet LAN

Brand : Zebra

Product code: ZE50043-LOE0000Z

Product name : ZE500

ZE500-4, LH, ZPL, 300dpi, 12dots/mm, 305mm/sec, 104mm (4.1"), 16MB/64MB, USB 2.0, RS-232, Parallel, ZebraNet 10/100, EU+UK PC, Black
Zebra ZE500. Maximum resolution: 300 x 300 DPI, Print speed: 305 mm/sec. Connectivity technology: Wired, Ethernet LAN, USB port. Product colour: Black



Printing		Design	
Maximum resolution *	300 x 300 DPI	Product colour *	Black
Print speed *	305 mm/sec	Built-in display	✓
Maximum printing width *	10.4 cm	Display *	LCD
Paper handling		Housing material	Metal
Ribbon width	10.7 cm	Power	
Ribbon length	600 m	Power requirements	90 - 264V AC, 47/63Hz
Maximum label width	11.4 cm	System requirements	
Maximum roll diameter	10.2 cm	Compatible operating systems	Windows 7 Windows XP Windows Vista Windows Server 2008 Windows Server 2003
Media thickness	0.254 mm	Operational conditions	
Media thickness (imperial)	0.010"	Operating relative humidity (H-H)	20 - 85%
Maximum media length	3.81 m	Storage relative humidity (H-H)	5 - 95%
Maximum media length (imperial)	150"	Operating temperature (T-T)	32 - 104 °F
Core diameter	2.54 cm	Operating temperature (T-T)	0 - 40 °C
Ports & interfaces		Storage temperature (T-T)	-40 - 71 °C
Connectivity technology *	Wired	Storage temperature (T-T)	-40 - 160 °F
Ethernet LAN *	✓	Weight & dimensions	
Wi-Fi *	✗	Width	245 mm
USB port *	✓	Depth	379 mm
USB 2.0 ports quantity	1	Height	300 mm
Parallel ports quantity	1	Weight	15.4 kg
RS-232 ports	1	Packaging content	
RS-232 interface	✓	Bundled software	ZebraDesigner Pro ZebraNet Bridge Enterprise ZBI 2.0 ZBI-Developer
Performance		Logistics data	
Page description languages	XML, ZPL, ZPL II	Harmonized System (HS) code	84433210
Internal memory	16 MB	Technical details	
Flash memory	64 MB	Sustainability certificates	ENERGY STAR
Built-in barcodes	1D, 2D, CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 49, Code 93, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, PDF417, POSTNET, QR Code, TLC39, UPC-A, UPC-E	Other features	
Built-in processor	Risc	Networking features	Fast Ethernet
Processor frequency	133 MHz		
Certification	IEC, EN, NRTL, CE, FCC, CCC, ICES, VCCI, NOM, KCC, BSMI, S-Mark, C-Tick, Gost-R		



8596375176317

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.