




APC Easy 3S uninterruptible power supply (UPS) Double-conversion (Online) 20 kVA 20000 W

Brand : APC

Product code: E3SUPS20KHB

Product name : Easy 3S

APC Easy 3S. UPS topology: Double-conversion (Online), Output power capacity: 20 kVA, Output power: 20000 W. Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 220 V. Form factor: Tower, Product colour: White, Display type: LED. Compliance certificates: RoHS, Certification: CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH. Width: 380 mm, Depth: 928 mm, Height: 1400 mm



Features		Design	
UPS topology *	Double-conversion (Online)	Display type	LED
Output power capacity *	20 kVA	International Protection (IP) code	IP20
Output power *	20000 W	Operational conditions	
Waveform *	Pure sine	Operating temperature (T-T)	0 - 40 °C
Input operation voltage (min) *	304 V	Storage temperature (T-T)	-15 - 40 °C
Input operation voltage (max) *	477 V	Operating relative humidity (H-H)	0 - 95%
Input frequency *	45/65 Hz	Storage relative humidity (H-H)	0 - 95%
Output operation voltage (min)	380 V	Operating altitude	0 - 999.9 m
Output operation voltage (max)	415 V	Non-operating altitude	0 - 15000 m
Output frequency	50/60 Hz	Certificates	
Maximum current	37 A	Compliance certificates	RoHS
Number of input phases	3	Certification	CE, EAC, IEC 62040-1-1, IEC 62040-2, IEC 62040-3, IEC 62040-4, ISTA 2B, RCM, WEEE, REACH
Number of output phases	3	Packaging content	
Input power factor	0.99	Management card included	✗
Output voltage Total Harmonic Distortion (THD)	3%	Quick installation guide	✓
Input current Total Harmonic Distortion (THD)	3%	Weight & dimensions	
Ports & interfaces		Width	380 mm
SmartSlot	✓	Depth	928 mm
SmartConnect port	✗	Height	1400 mm
Battery		Weight	122 kg
Battery technology	Sealed Lead Acid (VRLA)		

Battery		Packaging data	
Battery voltage	220 V	Package width	563 mm
Number of batteries supported	3	Package depth	1014 mm
Design		Package height	1640 mm
Form factor *	Tower	Package weight	158 kg
Product colour *	White	Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Output voltage	400 V



0731304340782



731304340782

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.