

ASUS Prime -750B-BLACK power supply unit 750 W 20+4 pin ATX ATX

Brand : ASUS

Product family: Prime

Product code: 90YE00Y0-B0NA00

Product name : PRIME-750B-BLACK

- Dual ball fan bearings that can last up to twice as long as sleeve bearing designs
 - An 80 Plus Bronze Certification is the result of low-ESR electrolytic capacitors and other premium components
 - Etched cables can be bent easily during installation
 - 6-year warranty included
- 750W, 80+ Bronze, ATX12V, Active PFC, 100-240Vac, 2.2 kg

ASUS Prime -750B-BLACK power supply unit 750 W 20+4 pin ATX ATX:

ASUS Prime 750W Bronze PSU brings efficient and durable power delivery to all-round PCs, and gaming rigs.

Prime Performance

With 80+ Bronze certification, dual ball fan bearings, etched cables and an 6-year warranty, the ASUS Prime series PSU brings efficient and durable power delivery to reliable performance for the system build.



Power		Ports & interfaces	
Total power *	750 W	CPU power connector (4+4 pin)	✓
AC input voltage *	100 - 240 V	CPU power cable length	80 cm
Power Factor Correction (PFC) type	Active	Cabling type	Non-Modular
Combined power (+3.3V)	120 W	Performance	
Combined power (+12V)	750 W	80 PLUS certification *	80 PLUS Bronze
Combined power (+5V)	120 W	Purpose *	PC
Combined power (-12V)	3.6 W	Power supply unit (PSU) form factor *	ATX
Combined power (+5Vsb)	12.5 W	Bearing technology	Ball bearing
Max output current (+3.3V)	20 A	Mean time between failures (MTBF)	120000 h
Max output current (+12V)	62.5 A	Design	
Max output current (+5V)	20 A	Product colour	Black
Max output current (-12V)	0.3 A	Cooling type	Active
Max output current (+5Vsb)	2.5 A	Fan diameter	13.5 cm
Power protection features	Over current, Over power, Over voltage, Short circuit, Under voltage	Number of fans	1 fan(s)
Ports & interfaces		Fan location	Top
Motherboard power connector *	20+4 pin ATX	On/off switch	✓
Motherboard power cable length	60 cm	Weight & dimensions	
Number of SATA power connectors	6	Width	150 mm
SATA power cable length	120,400 mm	Depth	150 mm
Peripheral (Molex) power connectors (4-pin) *	3	Height	86 mm
Peripheral (Molex) power cable length	120,400 mm	Weight	1.92 kg
PCI Express power connectors (8-pin)	3	Packaging data	
		Package width	340 mm
		Package depth	196 mm
		Package height	115 mm
		Package weight	3 kg

Packaging data

Package type

Box



4711387635124



0197105635128



197105635128

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.