



FSP FP 800 uninterruptible power supply (UPS) 0.8 kVA 480 W 2 AC outlet(s)

Brand : FSP

Product code: PPF4800401

Product name : FP 800

FP 600 - 800VA / 480W, 2-6 ms Transfer Time, 12 V / 9 AH battery

[FSP FP 800 uninterruptible power supply \(UPS\) 0.8 kVA 480 W 2 AC outlet\(s\):](#)

The line-interactive FP 800 UPS provides stable and reliable power protection. It is ideal for PC users or small business companies, as well as for small telecom applications.

The line-interactive FP 800 UPS with a compact size can provide stable power protection against surges and spikes. It is ideal for PC users or small business companies, as well as for small telecom applications. Its embedded microprocessor controller guarantees high reliability. It can automatically restart while AC power is recovering. With Simulated sine wave, off-mode charging, and cold start function, it will be a good choice.

FSP FP 800. Output power capacity: 0.8 kVA, Output power: 480 W, Waveform: Sine. AC outlet types: Type F, AC outlets quantity: 2 AC outlet(s). Battery capacity: 9 Ah, Battery voltage: 12 V, Battery recharge time: 6 h. Form factor: Tower, Product colour: Black. Width: 101 mm, Depth: 279 mm, Height: 142 mm



Features		Battery	
Output power capacity *	0.8 kVA	Battery capacity	9 Ah
Output power *	480 W	Battery voltage	12 V
Waveform *	Sine	Number of batteries supported	1
Input operation voltage (min) *	162 V	Battery recharge time	6 h
Input operation voltage (max) *	290 V	Cold start	✓
Input frequency *	50/60 Hz	Off-mode charging	✓
Output operation voltage (min)	220 V	Design	
Output operation voltage (max)	220 V	Form factor *	Tower
Automatic Voltage Regulation (AVR)	✓	Product colour *	Black
Noise level	40 dB	LED indicators	✓
Power protection features	Overcharge, Overload	Operational conditions	
Audible alarm(s)	✓	Operating temperature (T-T)	0 - 40 °C
Audible alarm modes	Battery replacement	Operating relative humidity (H-H)	0 - 90%
Auto-restart	✓	Weight & dimensions	
Ports & interfaces		Width	101 mm
AC outlet types	Type F	Depth	279 mm
AC outlets quantity	2 AC outlet(s)	Height	142 mm
		Weight	4.9 kg
		Logistics data	
		Harmonized System (HS) code	85078000



4711140489254

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.