

Axagon EE25-SL Screwless USB 3.2 Gen 1 - SATA 6G external box for 2.5" SSD/HDD

Brand : Axagon

Product code: EE25-SL

Product name : EE25-SL Screwless USB 3.2 Gen 1 - SATA 6G external box for 2.5" SSD/HDD

EE25-SL Screwless USB 3.2 Gen 1 - SATA 6G external box for 2.5" SSD/HDD

Axagon EE25-SL Screwless USB 3.2 Gen 1 - SATA 6G external box for 2.5" SSD/HDD. Product type: HDD/SSD enclosure. Number of storage drives supported: 1, Storage drive size: 2.5", Supported storage drive interfaces: Serial ATA, Serial ATA II, Serial ATA III. Data transfer rate: 5 Gbit/s. Product colour: Black. USB connector type: Micro-USB B



Storage		Power	
Number of storage drives supported *	1	External power adapter	✗
Storage drive size *	2.5"	System requirements	
Supported storage drive interfaces *	Serial ATA, Serial ATA II, Serial ATA III	Mobile operating systems supported	✓
Supported storage drive heights	7,9.5 mm	Windows operating systems supported	Windows 10, Windows 10 x64, Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows Vista, Windows Vista x64, Windows XP
NVMe	✗	Linux operating systems supported	Kernel 2.6, Kernel 2.6.31, Kernel 2.6.33
Ports & interfaces		Mac operating systems supported	Mac OS X 10.0 Cheetah, Mac OS X 10.1 Puma, Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
USB connectivity *	✓		
USB version	3.2 Gen 1 (3.1 Gen 1)		
USB connector type	Micro-USB B		
USB connector gender	Female		
USB ports quantity	1		
Design		Weight & dimensions	
Product type *	HDD/SSD enclosure	Width	82 mm
Product colour *	Black	Depth	16 mm
Material	Plastic	Height	130 mm
LED indicators	✓	Weight	63 g
Certification	CE, RoHS	Cable length	0.52 m
Performance		Package width	112 mm
Data transfer rate	5 Gbit/s	Package depth	20 mm
UASP support	✓	Package height	229 mm
TRIM support	✓	Package weight	132 g
S.M.A.R.T. support	✓	Packaging content	
Plug and Play	✓	Package type	Box
Power		AC adapter included	✗
Power source type	USB	Cables included	USB
		Manual	✓
		Technical details	
		Warranty period	2 year(s)
		Compliance certificates	RoHS

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2026. Prints or copies of Information are only valid on the printed Publication date